



Technical Data Sheet:

AKRIL SLOW

Code: 0017	Ref.: ST17	Revision: 3	Date: 05/07/2022
------------	------------	-------------	------------------

Product Characteristics:

Acrylic thinner formulated with high and medium boiling esters.

The high percentage of acetates used gives the product a characteristic fruit odor.

Formats: Drums 200 lt, Cans 25, 5 and 1 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm ³	0.860	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical
Index of refraction at 20°C	IR	1.443	Met. Int. ISTR. 46	± 0.005

Applications and Useful Information:

High-quality product made from pure raw materials specifically for acrylic and urethane bodywork paints, consisting of a metal-pigmented base layer and a transparent, glossy top coat.

Slowly evaporating, it is suitable for oven drying at high temperatures, as well as for use in high temperature and humidity conditions.

Chloride-free.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.