



Technical Data Sheet:

AKRIL REGULAR

Code: 0016	Ref.: ST16	Revision: 3	Date: 16/07/2020
-------------------	-------------------	--------------------	-------------------------

Product Characteristics:

Thinner for acrylic and urethane resin-based enamels, air and oven drying.

The high percentage of acetates used gives the product a good fruit odor.

Formats: Drums 200 lt, Cans 25, 5 and 1 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm ³	0.880	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Applications and Useful Information:

High-quality product made from pure raw materials specifically for acrylic and urethane bodywork paints, consisting of a metal-pigmented base layer and a transparent, glossy top coat. The sequence in the application of coats is facilitated by the speed of evaporation, which allows drying either by air or by oven drying at medium temperature, enhancing in both cases the effect of shine depth. It is also used for diluting pastel paints in cases where rapid drying is required or for performing simple touch-ups.

Chloride-free.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.