



Technical Data Sheet:

ALPINE

White spirit

Code: 0008	Ref.: ST08	Revision: 2	Date: 16/07/2010
------------	------------	-------------	------------------

Product Characteristics:

Denatured mineral white spirit.

Formats: Drums 200 lt, Cans 25, 5, 1, 0.5 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm ³	0.790	Met. Int. ISTR. 44	± 0.01
Water content	%	0.02	Met. Int. ISTR. 48	Maximum
Flash point	°C	31	Met. Int. ISTR. 53	Typical
Index of refraction at 20°C	IR	1.441	Met. Int. ISTR. 46	± 0.01

Applications and Useful Information:

For diluting synthetic and oleo-synthetic paints and enamels, oil paints and fine arts.

In addition to good solvent power, the slow evaporation gives the film perfect dilution and shine.

It is also used for cleaning surfaces before painting, as a dewaxing agent, as a solvent for oils and greases, for cleaning tar stains, for cleaning brushes and painting equipment, for DIY, etc.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

Not suitable for use in the car bodywork sector.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.