

Technical Data Sheet:

THINNER 2003

nitro anti-fog

 Code: 0019
 Ref.: ST19
 Revision: 8
 Date: 25/09/2017

Product Characteristics:

Thinner for nitrocellulose paints formulated partly with pure raw materials and partly with source pure raw materials.

Formats: Drums 200 lt, Cans 25, 20, 5 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Hazen	< 15	Comparison to STD	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm ³	0.820	Met. Int. ISTR. 44	± 0.04

Applications and Useful Information:

Specific thinner for washing and cleaning equipment in car body shops.

It is also a good nitro thinner dilute primers and rust inhibitors..

For good anti-bleaching power, 5 - 7% RETARDANT B corrective agent must be added.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application. Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.