



Technical Data Sheet:

Nitro thinner 21

Anti-fog

Code: D0034.0000O1	Ref.: ---	Revision: 5	Date: 19/10/2022
--------------------	-----------	-------------	------------------

Product Characteristics:

Anti-fog thinner for nitrocellulose paints formulated with technical raw materials.

Formats: Cans 1- 5- 18 - 20 - 25 liters.

Drums 200 liters.

Tanks 930 liters.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color	Hazen	< 15	Comparison to STD	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm ³	0.850	Met. Int. ISTR. 44	± 0.02

Applications and Useful Information:

Nitro thinner suitable for diluting primer paints, rust inhibitors and for general uses such as equipment washing and degreasing in metalwork.

To improve the anti-bleaching power, 5 - 7% RETARDANT B corrective agent must be added.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application. Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.