



## Technical Data Sheet:

# Thinner 709

*nitro anti-fog*

<b>Code:</b> 0077	<b>Ref.:</b> ST077	<b>Revision:</b> 7	<b>Date:</b> 01/03/2023
-------------------	--------------------	--------------------	-------------------------

### **Product Characteristics:**

Thinner for nitrocellulose paints formulated with pure raw materials and partly with source pure raw materials.

**Formats:** Drums 1000 lt, Drums 200 LT, Cans 25, 20 lt.

### **Technical Specifications:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color	Hazen	< 15	Comparison to STD	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm <sup>3</sup>	0.870	Met. Int. ISTR. 44	± 0.03

### **Applications and Useful Information:**

Economical nitro thinner suitable for diluting nitro primers and rust inhibitors.

Also suitable for general uses such as washing equipment and degreasing metalwork. To improve the anti-bleaching power, 5 - 7% RETARDANT B corrective agent must be added.

Dilute the enamel to the desired viscosity for the chosen application (brush or roller). Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

Not suitable for use in the car bodywork sector.

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.*