



Technical sheet:

DIL. POLIURETANICO 7029

Codice: 0013	Sigla: ST13	Revisione: 3	Data: 24/11/17
---------------------	--------------------	---------------------	-----------------------

Product Characteristics: A mixture of pure solvents with a characteristic fruit smell.

Formats: Drums 200 LT, Cans 25, 5 e 1 LT.

Technical specifications:

CHARACTERISTICS	UM	SPECIFIC VALUE	METHOD	TOLERANCE
Stato fisico	Liquid		Visual	//
Color	Clear colorless		Visual	//
Density at 20°C	Kg/dm ³	0,863	Met. Int. ISTR. 44	± 0,005
Water Content	%	0.3	Met. Int. ISTR. 48	Maximun
Flash Point	°C	< 0	Met. Int. ISTR. 53	Tipical

Applications and Useful Information:

For the dilution of catalyzed polyurethane varnishes of medium quality and primer

Under unfavorable temperature and / or humidity conditions, it is advisable to mix the product with Retarder B up to a maximum of 20%.

Dilute the paint to obtain the optimal viscosity for the chosen application: denser for brush or roller or more liquid for spray application.

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the OV SpA control.