



Technical Data Sheet:

UNIVERSAL THINNER 611

Code: 0104	Ref.: ST0104	Revision: 0	Date: 14/09/2018
------------	--------------	-------------	------------------

Product Characteristics:

Multi-purpose thinner formulated with pure raw materials based on ketones, aromatic solvents, alcohols and esters. It has high solvent power and is fast drying.

Formats: Tanks 1000 lt, Drums 200 lt, Cans 25, 5 and 1 lt.

Technical specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm ³	0.850	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Applications and Useful Information:

Specific product for diluting fast-drying and nitrosynthetic enamels.

And also:

Because of its peculiar VERSATILITY, it can also be used for most nitrocellulose, chlorocarbon, epoxy, acrylic, antifouling and synthetic paints, while for oil-synthetic paints it can be used only for the first coat.

It is widely used in the engineering industry, in painting earthmoving machinery and in all cases where high solvent power and rapid drying are required.

Because of its high solvent power, the product can be used for gluing plastics.

It is also excellent for cleaning painting equipment.

For degreasing, washing and cleaning operations in the bodywork sector, please refer to products that comply with Italian Legislative Decree No. 161 of March 27, 2006.

Dilute the enamel to the optimum viscosity for the chosen equipment, mix thoroughly, especially for epoxy paints.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.