



Technical Sheet:

ECO DILUENT

Code: 0006	Sigla: ST06	Revision: 6	Date: 09/02/2018
------------	-------------	-------------	------------------

Product Characteristics:

Universal thinner with a pleasant fruity smell, characteristic of the acetates.

Formats:

200 - 25 - 20 - 5 - 1 liters.

Technical Specifications:

CHARACTERISTICS	UM	VALUE	METHOD	TOLLERANCE
Physical Aspect		Liquide	Visual	//
Color		Clear Colorless	Visual	//
Density at 20°C	Kg/dm ³	0,830	Met. Int. ISTR. 44	± 0,005
Water Content	%	0.3	Met. Int. ISTR. 48	Max
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Use / Applications:

UNIVERSAL product with a high anti-fogging power formulated with high quality raw materials, which give distension and shine to the paint. Suitable for diluting all types of paints: nitrocellulose, acrylic, epoxy, synthetic, fast drying synthetic, polyurethane.

The absence of aromatic and chlorinated hydrocarbons ensures the utmost respect for the operator and the environment.

Dilute the paint until obtaining the optimal viscosity for the chosen application. Thicker for the brush or roller, more liquid for spray application. Approximately between 10 and 20%, unless otherwise indicated printed on the can.

The product complies with the Legislative Decree No. 161 of 27 of March, 2006 for the limitation of emissions V.O.C. (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Product limit value ready to use (g / l) - Legislative Decree no. 161/06
Preparatory and cleaning products	Preparatory product	850

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the OV SpA control.