



Technical Data Sheet:

EUROS

nitro anti-fog thinner

Code: 0003	Ref.: ST03	Revision: 6	Date: 21/10/2019
------------	------------	-------------	------------------

Product Characteristics:

Nitrocellulose paint thinner, formulated with pure raw materials, very faint and tolerable odor. It contains a high percentage of acetates and glycols.

Formats: Drums 200 lt, Cans 25, 5 and 1 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm ³	0.840	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Applications and Useful Information:

Excellent thinner for nitro, nitrosynthetic and acrylic enamels. Chloride-free. It gives the paint excellent flow and shine. It has a high anti-bleaching power. Its versatility also makes it suitable for diluting antifouling paints, nitro building insulation, nitro wood paints, and epoxy paints.

Dilute the enamel to the desired viscosity for the chosen application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.