



Technical Data Sheet:

L11/E

nitro anti-fog thinner

Code: 0007	Ref.: ST07	Revision: 7	Date: 22/02/2017
------------	------------	-------------	------------------

Product Characteristics:

Nitrocellulose paint thinner, formulated with pure raw materials, faint and tolerable odor.

Formats: Drums 200 lt, Cans 20, 20 lt.

Technical specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Density at 20°C	Kg/dm ³	0.840	Met. Int. ISTR. 44	± 0.010

Applications and Useful Information:

It is a versatile thinner suitable for diluting nitrocellulose paints, rust inhibitors, fast-drying synthetic paints. To improve the anti-bleaching power, 5 - 7% RITARDANTE B corrective agent must be added. Suitable for cleaning equipment.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application. Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.