



## Technical Data Sheet:

# MELIUS

*nitro anti-fog thinner*

Code: 0005	Ref.: ST05	Revision: 5	Date: 21/10/2019
------------	------------	-------------	------------------

### Product Characteristics:

Nitrocellulose paint thinner, formulated with pure raw materials, faint and tolerable odor.

**Formats:** Drums 200 lt, Cans 25, 20, 5 and 1 lt.

### Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm <sup>3</sup>	0.845	Met. Int. ISTR. 44	± 0.005
Water content	%	0.3	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

### Applications and Useful Information:

Excellent anti-fog, chloride-free nitro thinner suitable for diluting nitrocellulose paints, epoxy paints, antifouling paints, nitro for wood, nitro building insulation, fast-drying enamels. It gives the paint good flow and shine.

Dilute the enamel to the desired viscosity for the chosen application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.*