



Scheda Tecnica:

NITROL

nitro anti-fog thinner

Codice: 0004	Sigla: ST04	Revisione: 7	Data: 22/02/17
---------------------	--------------------	---------------------	-----------------------

Product Characteristics:

Thinner for Nitrocellulose paints, formulated with pure raw materials, with a soft and tolerable odor.

Formats:

Drums 200 liters,

Cans 25 - 20 - 5 - 1 liters.

Technical Specifications of the Product:

CHARACTERISTICS	UM	METHOD	VALUE	TOLERANCE
Physical State	Liquid		Visual	//
Color	Colorless		Visual	//
Flash Point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Water Content	%	0.3	Met. Int. ISTR. 48	Max
Density at 20°C	Kg/dm ³	0,840	Met. Int. ISTR. 44	± 0,010

Use / Applications:

It gives the paint distension and shine. To increase the anti-fogging power, add 3 to 5% of Retardant B. Suitable for cleaning equipment.

Dilute the paint until obtaining the optimal viscosity for the chosen application. Thicker for brush or roller and more liquid for spray application. Approximately between 10 and 20%, unless otherwise indicated on the paint can.

The product complies with the Legislative Decree No. 161 of 27 of March, 2006 for the limitation of emissions V.O.C. (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Product limit value ready to use (g / l) - Legislative Decree no. 161/06
Preparatory and cleaning products	Preparatory product	850

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the OV SpA control.