

## **Product Characteristics:**

Thinner for nitrocellulose coatings formulated in part with pure raw materials and partly with regenerated raw materials.

## *Formats:* Drums 200 LT- Cans 25- 20 5- 1- 0,5 LT.

## **Technical Specifications:**

CHARACTERISTICS	UM	VALUE	METHOD	TOLERANCE
Physical Aspect		Liquido	Visivo	//
Color	Hazen	< 15	Confronto a STD	//
Flash Point	°C	< 0 (vaso chiuso)	Met. Int. ISTR. 53	11
Density at 20°C	Kg/dm <sup>3</sup>	0,830	Met. Int. ISTR. 44	± 0,02

## Use / Applications:

Specific thinner for gun washing and cleaning of equipment in the bodywork.

It is also a good solvent for the dilution of funds and rust inhibitors.

To increase the anti-fog power, add 5-7% of RITARDANTE B.

Dilute the paint to obtain the optimal viscosity for the chosen application. Denser for brush or roller and more liquid for spray application. Approximately between 10 and 20%, unless otherwise indicated on the paint container.

The product complies with the Legislative Decree No. 161 of 27 of March, 2006 for the limitation of emissions V.O.C. (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Product limit value ready to use (g / l) - Legislative Decree no. 161/06
Preparatory and cleaning products	Preparatory product	850

The above information is given according to our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the OV SpA control.