

Technical Data Sheet:

PETROLEUM

Code: 1069 | Ref.: ST1069 | Revision: 1 | Date: 17/06/2009

Product Characteristics:

Blend of high-boiling aliphatic hydrocarbons, with a characteristic odor of petroleum products.

Formats: Cans 1 lt

Technical Specifications:

| CHARACTERISTIC | METHOD | UM | VALUE |
|--------------------------|---------------|-------------------|----------|
| Physical state | ASTM D 4176/1 | Liquid, clear | |
| Color | ASTM D 156 | max | 20 |
| Flash point | ASTM D 3828/A | °C | > 38°C |
| Boiling point | ASTM D 86 | °C | 140 |
| Distillation range | ASTM D 86 | °C | 140- 300 |
| Density at 15°C | ASTM D 1298 | Kg/m ³ | 770- 820 |
| Explosive limits | lower than | % vol | 0.7 |
| | higher than | % vol | 5 |
| Autoignition temperature | DIN 51794 | °C | + 200 |

Applications and Useful Information:

This product is perfect for cleaning grease and oily residues from any painted and unpainted surface, rubber and plastic surfaces.

It removes tar from automobile bodies and is suitable for cleaning floors, machine tools and motor parts. It is also particularly suitable for cleaning rubber rollers and clichés of printing machines using grease inks.

It can be applied by using a brush or a rag.

Not suitable for use in the car bodywork sector.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.