



Technical Data Sheet:

**WATER-BASED
DEGREASER 2100**

Code: 0053	Ref.: ST53	Revision: 2	Date: 16/07/2010
-------------------	-------------------	--------------------	-------------------------

Product Characteristics:

Water-based degreaser for metals and plastics, with low solvent content, characterized by faint and tolerable odor.

Formats: Plastic containers of 20 and 5 liters.

Technical specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Flash point	°C	28	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm ³	0.970	Met. Int. ISTR. 44	± 0.005
Index of refraction at 20°C	IR	1.355	Met. Int. ISTR. 46	± 0.005

Applications and Useful Information:

Product for degreasing all metals and polished surfaces such as stainless steel. The product removes medium-light lubricating grease, handprints, dirt and various contaminants and is particularly suitable for degreasing before painting the workpiece with both solvent and water-based products. Its special formulation allows the product to be medium-fast drying, which leaves no water residue on the treated surface. It is also suitable for degreasing plastic materials and painted surfaces, as it does not affect or matte them.

The product can be applied by spray, brush and rag. In the case of particularly stubborn grease, repeat the application several times by removing the contaminant with a dry rag. Evaporation of the product can be accelerated by blowing compressed air over the degreased part.

Ensure complete drying of the product before painting the surfaces.

Dilution: The product is ready to use, but it can still be diluted with water for very light degreasing as needed.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

<i>Product</i>	<i>Function</i>	<i>Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06</i>
Preparation and cleaning products	Preparation product	850

V.O.C. of the product: Max 250 g/L.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.