



Technical Data Sheet:

SYNTEK synthetic thinner

Code: 0009	Ref.: ST09	Revision: 4	Date: 29/04/2020
-------------------	-------------------	--------------------	-------------------------

Product Characteristics:

Thinner for synthetic paints composed of petroleum-extracted aliphatic solvents.

Formats: Drums 200 lt, Cans 25, 5, 1, 0.5 lt.

Technical Specifications:

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Density at 20°C	Kg/dm ³	0.795	Met. Int. ISTR. 44	± 0.01
Water content	%	0.1	Met. Int. ISTR. 48	Maximum
Flash point	°C	< 0	Met. Int. ISTR. 53	Typical

Applications and Useful Information:

Suitable for diluting synthetic enamels, rust inhibitors and synthetic primers. The solvent power of the formulation is greater than traditional white spirit. It allows perfect flow without leaving brush marks. It can also be used in cleaning equipment and brushes.

It can be used as a degreaser and cleaner of supports before painting and for cleaning equipment.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application. Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

Not suitable for use in the car bodywork sector.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.