



## Technical Data Sheet:

# SYNTEK S

*synthetic universal thinner*

<b>Code:</b> 0027	<b>Ref.:</b> ST27	<b>Revision:</b> 7	<b>Date:</b> 15/01/2021
-------------------	-------------------	--------------------	-------------------------

### **Product Characteristics:**

Universal thinner for synthetic paints composed of petroleum-extracted aliphatic solvents.

**Formats:** Drums 200 lt, Cans 25, 5, 1 lt.

### **Technical Specifications:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state	Liquid		Visual	//
Color	Colorless clear		Visual	//
Density at 20°C	Kg/dm <sup>3</sup>	0.810	Met. Int. ISTR. 44	± 0.01
Water content	%	0.10	Met. Int. ISTR. 48	Maximum

### **Applications and Useful Information:**

Product having high solvent power, especially designed for the dilution of all synthetic paints including fast-drying, antifouling and chlorine paints. The evaporation speed is higher than regular white spirit, but still ensures perfect flow and shine without leaving brush marks.

It can be used as a degreaser and cleaner of supports before painting and for cleaning equipment.

Dilute the enamel to the desired viscosity for the chosen application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

The product complies with Italian Legislative Decree No. 161 of March 27, 2006 for the limitation of emissions of VOCs (volatile organic compounds) resulting from the use of bodywork products.

Product	Function	Limit value of ready-to-use product (g/l) - Legislative Decree No. 161/06
Preparation and cleaning products	Preparation product	850

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.*