



## Technical Data Sheet:

# THINNER 30

*nitro anti-fog*

<b>Code:</b> 0061	<b>Ref.:</b> ST61	<b>Revision:</b> 7	<b>Date:</b> 02/02/2022
-------------------	-------------------	--------------------	-------------------------

### **Product Characteristics:**

Thinner for nitrocellulose paints formulated partly with pure raw materials and partly with source pure raw materials.

**Formats:** Tanks 930 lt, Drums 200 lt, Cans 25, 20 and 5 lt.

### **Technical Specifications:**

CHARACTERISTIC	UM	VALUE	METHOD	TOLERANCE
Physical state		Liquid	Visual	//
Color		Colorless clear	Visual	//
Flash point	°C	< 0 (closed cup)	Met. Int. ISTR. 53	//
Density at 20°C	Kg/dm <sup>3</sup>	0.850	Met. Int. ISTR. 44	± 0.02
Water	%	< 0.5%	Met. Int. ISTR. 48	//

### **Applications and Useful Information:**

Economical, yet balanced formulation nitro anti-fog thinner.

Suitable for diluting nitro paints, both primer and topcoat, rust inhibitors and general uses such as equipment washing and degreasing in metalwork.

To improve the anti-bleaching power, 5 - 7% RITARDANTE B corrective agent must be added.

Dilute the enamel to the desired viscosity for the chosen application. Thicker for brush or roller, more liquid for spray application.

Approximately between 10 and 20 %, unless there are different indications printed on the paint can.

*The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.*