

#### Technical Data Sheet:

# **QUOD**

straw oil

Code: 0030 | Ref.: ST30 | Revision: 1 | Date: 17/06/2009

#### **Product Characteristics:**

Blend of denatured synthetic oils (alkylbenzoles) with an extremely faint odor and a straw color.

**Formats:** Drums 200 lt, Cans 25, 5, 1 and 0.5 lt.

## **Technical Specifications:**

| CHARACTERISTIC      | METHOD              | UM     | VALUE |
|---------------------|---------------------|--------|-------|
| Physical state      | Liquid, Clear amber |        |       |
| Color               | ASTM D 1500         |        | 1.5   |
| Flash point         | ASTM D 93           | °C     | 160   |
| Water content       | ASTM D 1533         | p.p.m. | 100   |
| Density at 20°C     | ASTM D 4052         | Kg/l   | 0893  |
| Viscosity at 50°C   | ASTM D 445          | cSt    | 12.7  |
| Index of refraction | ASTM D 1218         |        | 1494  |

### **Applications and Useful Information:**

It brightens and nourishes furniture varnish, protects virgin wood, and is used as an impregnating agent for porous floors and concrete artifacts. It can also be used in interiors, because it is a synthetic oil and even in the presence of mold and bacteria there is no risk of bad odors caused by the rancidity of fatty acids in vegetable products.

It is particularly suitable for polishing anodized aluminum window frames, reviving and restoring plastic shutters as well as all plastic parts of boats, mopeds, etc., discolored by the sun.

The above information is provided based on our theoretical and practical knowledge. The company, however, does not assume any liability as the conditions of use and application are not subject to the control of OV SpA.